



Years Warranty\*

## ANSMANN Lithium 2

Charger for 1-2 Li-Ion rechargeable batteries (3.6V/3.7V) 26650, 22650, 18650, 18500, 17670, 16340, 14500 etc. or 1-2 NiMH rechargeable batteries (1.2V) AA / AAA

### Features

- Charger for 1-2 Li-Ion rechargeable batteries (3.6V/3.7V) 26650, 22650, 18650, 18500, 17670, 16340, 14500 etc. or 1-2 NiMH rechargeable batteries (1.2V) AA / AAA
- Including USB-C charge cable
- Single slot monitoring
- Automatic detection of Li-Ion and NiMH rechargeable batteries
- Charging starts automatically once the batteries have been inserted with the correct polarity
- Microcontroller-monitored charge control (CC-CV with Li-Ion, 0dV/-dV with NiMH)
- Automatic battery-full detection and termination of the charge process
- Maintenance charging for NiMH batteries
- Indication of the charge status via 3 LEDs per charge slot
- Indication of incorrectly inserted batteries (wrong polarity)
- Operation via 5V DC USB adapter (not included)
- 3 years guarantee



Charging current



Single Shaft Monitoring



Automatic Shutdown



Powered by USB



Article number: 1001-0050

Product content: Lithium 2, USB-C cable, operating instructions



## Specifications

Input voltage	5V DC
For worldwide use	Yes
Chargeable cell chemistry	Nickel metal hydride / Nickel-cadmium / Lithium
Chargeable cells	AAA / HR03 / AA / HR6 / 26650 / 26500 / 25500 / 22650 / 22500 / 21700 / 20700 / 18700 / 18650 / 18500 / 18490 / 18350 / 17670 / 17650 / 17500 / 17350 / 16650 / 16500 / 16340 / RCR123 / 14650 / 14500 / 14430 / 14350 / 13650 / 13500 / 13450 / 12650 / 12500 / 12340 / 10500 / 10440 / 10350 / 10340
Charging current AAA	500 mA (1-2)
Charging current AA	500 mA (1-2)
Charging current lithium	1000 mA (1-2)
Microprocessor control	Yes
Safety timer	Yes
Single shaft monitoring	Yes
Overload protection	Yes
Color	black
Packaging	box
Operating temperature	0 - 35 °C
Storage temperature	0 - 40 °C