

Technical Specification

Lithium-thionyl Chloride (Li-SOCl₂) Battery



ER14505

AA – size bobbin cell

ELECTRICAL CHARACTERISTICS

(typical values for cells stored for one year or less, at 25°C)

Nominal Capacity	2,70 Ah
-------------------------	----------------

(At 1 mA, +25°C, 2.0V cut off. The capacity restored by the cell varies according to current drain, temperature and cut off voltage.)

Nominal Voltage	3,6V
------------------------	-------------

Maximum recommended continuous current	40mA
-----------------------------------------------	-------------

(To get 50% of the nominal capacity at +25°C with 2V cut off. Higher currents possible, consult EUROPA Batteries.)

Pulse capability: Typically up to 150mA (150mA/0.1 second pulses, drained every 2 min at 25°C from undischarged cells with 10µA base current, yield voltage readings above 3.0V. The readings may vary according to the pulse characteristics, the temperature, and the cell's previous history. Fitting cell with a capacitor may be recommended in severe conditions. Consult EUROPA Batteries.)

Storage (recommended)	30°C max
------------------------------	-----------------

(for more severe condition consult EUROPA Batteries)

Operating temperature range	-60°C / +85°C
------------------------------------	----------------------

(Operation at temperature different from ambient may lead to reduced capacity and lower voltage plateau readings)

Typical weight	19g
-----------------------	------------

KEY FEATURES

- ✓ High and stable operating voltage
- ✓ High minimum voltage during pulsing
- ✓ Low self discharge rate (less than 1% after 1 year of storage at +25°C)
- ✓ Stainless steel container
- ✓ Hermetic glass-to-metal sealing
- ✓ Non-flammable electrolyte
- ✓ Non-restricted for transport (class9)
- ✓ Compliant with IEC 86-4 safety standard and EN 50020 intrinsic safety

 Underwriters Laboratories (UL)
Component Recognition
(File Number MH28717)

MAIN APPLICATIONS



- ✓ Utility metering
- ✓ Alarms and security devices
- ✓ Memory back-up
- ✓ Tracking systems
- ✓ Automotive electronics
- ✓ Professional electronics
- ...etc.

WARNING:


Fire, explosion and severe burn hazard. Do not recharge, crush, disassemble, heat above 100°C, incinerate, or expose contents to water.

Note: Any representations in this data sheet concerning performance are informational purpose only and are not construed as warranties, either expressed or implied, of future performance.

1. DISCHARGE CHARACTERISTICS @25°C



2. VOLTAGE VS. TEMPERATURE




AVAILABLE TERMINATIONS

Suffix-/S	Standard
Suffix-/P	Axial Pins
Suffix-/T	Solder Tabs
Suffix-/2PT	Radial Pins
Suffix-/3PT/3TP	Radial Pins

[View available terminations](#)

3. CAPACITY VS. CURRENT



4. STORAGE CHARACTERISTICS

